

Irrigation, Pumps, Reverse

Osmosis (RO), Water Filters /

Filtration, Water Chillers, Sprayers,

Tubing, Filters, Pond, etc > Water Filtration, Reverse Osmosis (RO)

Systems, etc.

DM-2 Industrial Dual TDS Monitor

HorticultureSource.com

Irrigation, Pumps, Reverse

Osmosis (RO), Water Filters /

Filtration, Water Chillers, Sprayers,

Tubing, Filters, Pond, etc > Water Filtration, Reverse Osmosis (RO)

Systems, etc.

DM-2 Industrial Dual TDS Monitor

Model: hf-HLTDS

DM-2 Industrial Dual TDS Monitor

Manufacturer: Hydro-Logic

Hydro-Logic DM-2 Industrial Dual TDS Monitor (HLTDS) Measure the untreated water coming in vs. the purified water going out of your Reverse Osmosis system at any time. This is important in determining when the RO membranes need to be changed. Auto-Off function conserves battery power. The unit shuts off automatically after 20 seconds. 90 ppm, the resolution is in 10 ppm increments, indicated by a blinking 'x10' image. Factory calibrated: all meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated. Comes equipped with a 1/2" inlet and 3/8" outlet. Quick Connect T-fittings for Merlin-Garden Pro or Tall Blue-Merlin for quick install.

Manufacturer's Product Information

MSRP each \$75

UPC812111010362

Dimensions1.5 x 1 x 3.2

Case Weight2

Case Quantity5

Price: \$48.15